

SX-15



► FEATURES

- Looping video inputs for multiple connections
- Auto termination
- Quick signal-switching time
- Supports color and B/W picture
- NTSC/PAL/SECAM scan system compatible
- Selectable signal source
- PC compatible
- Auto-adjustment for optimal setting
- NeoV Optical Glass™
- Distinctive aluminum alloy housing for added strength
- Kensington® security socket
- VESA standard wall mount



► SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	15" (381mm)
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297mm
	Brightness	400cd/m ² (Typical)
	Contrast Ratio	500:1 (Typical)
	Viewing Angle (H/V)	140°/130° (Typical)
	Display Color	16.7M
	Response Time	12ms (GTG)
	Frequency (H/V)	H: 30kHz - 60kHz V: 50Hz - 75Hz
Input Connector	Max. Pixel Clock	80MHz
	Life Time	30,000hrs (Minimum)
	Analog	15-Pin D-Sub
Input Signal	Digital	29-Pin DVI-D
	BNC Security	BNC Connector
	Analog	RGB H.V Sync
Output Connector	Digital	TMDS
	Auto Composite System	NTSC/PAL/SECAM
	BNC Security	BNC Connector
NeoV Optical Glass	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ +20°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/BAURT, CE, BSMI, ISO 13406-2, GOST, WEEE, RoHS
Power	VESA	DDC 1/2B, DPMS
	Power Source	100 - 240V, 50 - 60Hz
	Consumption	<48W (On) <4W (Stand-by) <2W (Off)
Temperature	Operation	0°C ~ 40°C
Dimensions	Net (W x H x D)	380 x 155 x 359mm (15.0" x 6.1" x 14.1")
	Packing (W x H x D)	438 x 210 x 470mm (17.2" x 8.3" x 18.5")
Weight	Net Weight	4.8Kg (10.6 lbs)
	Gross Weight	7.0Kg (15.4lbs)
Packing	1 Pallet	40 Cartons
	20' Container	480 Sets
	40' Container	1040 Sets

All specifications are subject to change without prior notice